

# API <https://api.politie.nl>

All methods: GET

All parameters: query parameters, except when indicated "header". (\* indicates required parameter)

Responses Content type: application/json

## available uri's:

1. /v4/politiebureaus (Search police stations)
2. /v4/politiebureaus/all (Retrieve all police stations)
3. /v4/nieuws (Search all news messages)
4. /v4/nieuws/lokaal (Search all local news messages)
5. /v4/wijkagenten (Search local officers)
6. /v5/gezocht-zaak (Search a single APB by UID.)
7. /v5/vermist-zaak (Search a single missing person by UID.)
8. /v5/gezocht (Search all APB's.)
9. /v5/gezocht/eigenaar-gezocht (Search all APB's on stolen and recovered goods)
10. /v5/gezocht/opsporingsbericht (Search wanted persons)
11. /v5/gezocht/nationale-opsporingslijst (Search all fugitive APB's)
12. /v5/gezocht/getuigenoproep (Search all calls for witnesses)
13. /v5/vermist (Search all missing persons)
14. /v5/vermist/ongeïdentificeerde-personen (Search unidentified persons)
15. /v5/urgentpolitiebericht (Show urgent APB when issued)

## Description of use:

### 1. /v4/politiebureaus

Search police stations in the near vicinity of a given GPS coordinate. Results are sorted on ascending distance from the coordinate... If no data is found within the given radius, the radius is expanded (up to 25 km) until data is found.

## Parameters

lat \* (string)

Latitude of the GPS coordinate used for search.

lon \* (string)

Longitude of the GPS coordinate used for search.

Radius (string)

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0, 10.0 and 25.0. Default value : 5.0

Maxnumberofitems (string)

Maximum number of objects to return. Allowed values are 10 and 25. Default value : 10

Offset (string)

Offset of the first object in this set (skipped items). This value must be a multiple of maxnumberofitems.

Default value : 0

## Example

<https://api.politie.nl/politiebureaus/v1?lat=53.1511173&lon=6.7566345999999984&radius=5.0&maxnumberofitems=10&offset=0>

## Responses

200: successful operation:

Example Value

Model

```
{
  "iterator": {
    "last": true,
    "offset": 0
  },
  "politiebureaus": [
    {
      "name": "string",
      "displayName": "string",
      "path": "string",
      "primaryNodeTypeName": "string",
      "leaf": true,
      "links": [
        {
          "rel": "string",
          "type": "string",
          "href": "string",
          "title": "string"
        }
      ],
      "canonicalHandleUuid": "string",
      "localizedName": "string",
      "uid": "string",
      "publicatieDatum": "string",
      "url": "string",
      "translations": [
        {
          "language": "string",
          "id": "string"
        }
      ],
      "naam": "string",
      "bezoekadres": {
        "postAdres": "string",
        "postcode": "string",
        "plaats": "string"
      },
      "postadres": {
        "postAdres": "string",
        "postcode": "string",
        "plaats": "string"
      },
      "openingstijden": "string",
      "telefoonnummer": "string",
      "faxnummer": "string",
      "twitterUrl": "string",
      "facebookUrl": "string",
      "extraInformatie": "string",
      "afbeelding": {
        "url": "string",
        "altText": "string"
      }
    }
  ]
}
```

```

    },
    "locatie": [
      {
        "latitude": 0,
        "longitude": 0
      }
    ]
  }
]
}

```

204: No results found

400: Invalid parameter:

Example Value  
Model

```

{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}

```

## 2. *lv4/politiebureaus/all*

Retrieve all police stations currently operational. Results are unsorted. Items are returned in chunks of max 100.

### **Parameters**

Offset (string)

Offset of the first object in this set (skipped items). This value must a multiple of 100. Default value : 0

### **Example**

<https://api.politie.nl/v4/politiebureaus/all?offset=0>

### **Responses**

200: successful operation:

Example Value

Model

```

{
  "iterator": {
    "last": true,
    "offset": 0
  },
  "politiebureaus": [
    {
      "name": "string",
      "displayName": "string",
      "path": "string",
      "primaryNodeTypeName": "string",
      "leaf": true,
      "links": [

```

```

    {
      "rel": "string",
      "type": "string",
      "href": "string",
      "title": "string"
    }
  ],
  "canonicalHandleUuid": "string",
  "localizedName": "string",
  "uid": "string",
  "publicatieDatum": "string",
  "url": "string",
  "translations": [
    {
      "language": "string",
      "id": "string"
    }
  ],
  "naam": "string",
  "bezoekadres": {
    "postAdres": "string",
    "postcode": "string",
    "plaats": "string"
  },
  "postadres": {
    "postAdres": "string",
    "postcode": "string",
    "plaats": "string"
  },
  "openingstijden": "string",
  "telefoonnummer": "string",
  "faxnummer": "string",
  "twitterUrl": "string",
  "facebookUrl": "string",
  "extraInformatie": "string",
  "afbeelding": {
    "url": "string",
    "altText": "string"
  },
  "locatie": [
    {
      "latitude": 0,
      "longitude": 0
    }
  ]
}

```

204: No results found

400: Invalid parameter:

Example Value

Model

```

{
  "code": 0,
  "type": "string",

```

```

"message": "string",
"invalidFields": [
  "string"
]
}

```

### 3. *lv4/nieuws*

Search news messages. The resultsets contains all messages. Use nieuws/lokaal to retrieve local news only. Results are sorted on descending date (newest first). A maximum of 200 messages is returned.

#### **Parameters**

uid (string)

Uid of document or page

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

Default value : nl

query (string)

Terms to query for. Length of the query is limited to 100 characters.

fromdate (string)

Select only messages newer than given date (including). Dateformat is YYYYMMDD.

todate (string)

Select only messages older than given date (including). Dateformat is YYYYMMDD.

lat (string)

Latitude of the GPS coordinate used for search.

lon (string)

Longitude of the GPS coordinate used for search.

radius (string)

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

Default value : 5.0

maxnumberofitems (string)

Maximum number of objects to return. Allowed values are 10 (default) and 25.

Default value : 10

offset (string)

Offset of the first object in this set (skipped items). This value must a multiple of maxnumberofitems.

Default value : 0

#### **Example**

<https://api.politie.nl/v4/nieuws?language=nl&query=drie%20personen&radius=5.0&maxnumberofitems=10&offset=0>

#### **Responses**

200: successful operation

Example Value

Model

```

{
  "iterator": {

```

```

    "last": true,
    "offset": 0
  },
  "nieuwsberichten": [
    {
      "name": "string",
      "displayName": "string",
      "path": "string",
      "primaryNodeTypeName": "string",
      "leaf": true,
      "links": [
        {
          "rel": "string",
          "type": "string",
          "href": "string",
          "title": "string"
        }
      ],
      "canonicalHandleUuid": "string",
      "localizedName": "string",
      "uid": "string",
      "publicatieDatum": "string",
      "url": "string",
      "translations": [
        {
          "language": "string",
          "id": "string"
        }
      ],
      "titel": "string",
      "introducectie": "string",
      "gebied": "string",
      "alineaas": [
        {
          "alineaType": "string"
        }
      ],
      "afbeelding": {
        "url": "string",
        "altText": "string"
      },
      "locaties": [
        {
          "latitude": 0,
          "longitude": 0
        }
      ],
      "urlTipformulier": "string",
      "uidTipformulier": "string"
    }
  ]
}

```

204: No results found

400: Invalid parameter

Example Value

Model

```
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```

#### 4. **/v4/nieuws/lokaal**

Search local news messages. The resultsets contains local messages. Use nieuws to retrieve all news. Results are sorted on descending date (newest first). A maximum of 200 messages is returned.

##### **Parameters**

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

Default value : nl

query (string)

Terms to query for. Length of the query is limited to 100 characters.

fromdate (string)

Select only messages newer than given date (including). Dateformat is YYYYMMDD.

todate (string)

Select only messages older than given date (including). Dateformat is YYYYMMDD.

lat \* (string)

Latitude of the GPS coordinate used for search.

lon \* (string)

Longitude of the GPS coordinate used for search.

radius (string)

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

Default value : 5.0

maxnumberofitems (string)

Maximum number of objects to return. Allowed values are 10 (default) and 25.

Default value : 10

offset (string)

Offset of the first object in this set (skipped items). This value must a multiple of maxnumberofitems.

Default value : 0

##### **Example**

<https://api.politie.nl/v4/nieuws/lokaal?language=nl&lat=53.15&lon=6.75&radius=5.0&maxnumberofitems=10&offset=0>

##### **Responses**

200: successful operation

Example Value

Model

```
{
```

```

"iterator": {
  "last": true,
  "offset": 0
},
"nieuwsberichten": [
  {
    "name": "string",
    "displayName": "string",
    "path": "string",
    "primaryNodeTypeName": "string",
    "leaf": true,
    "links": [
      {
        "rel": "string",
        "type": "string",
        "href": "string",
        "title": "string"
      }
    ],
    "canonicalHandleUuid": "string",
    "localizedName": "string",
    "uid": "string",
    "publicatieDatum": "string",
    "url": "string",
    "translations": [
      {
        "language": "string",
        "id": "string"
      }
    ],
    "titel": "string",
    "introduction": "string",
    "gebied": "string",
    "alineaas": [
      {
        "alineaType": "string"
      }
    ],
    "afbeelding": {
      "url": "string",
      "altText": "string"
    },
    "locaties": [
      {
        "latitude": 0,
        "longitude": 0
      }
    ],
    "urlTipformulier": "string",
    "uidTipformulier": "string"
  }
]
}

```

204: No results found

400: Invalid parameter

Example Value

```

Model
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}

```

## 5. /v4/wijkagenten

Search local officers in the near vicinity of a given GPS coordinate. Results are sorted on ascending distance from the coordinate. If no data is found within the given radius, the radius is expanded (up to 25 km) until data is found.

### Parameters

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

Default value : nl

lat \* (string)

Latitude of the GPS coordinate used for search.

lon \* (string)

Longitude of the GPS coordinate used for search.

radius (string)

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

Default value : 5.0

maxnumberofitems (string)

Maximum number of objects to return. Allowed values are 10 (default) and 25.

Default value : 10

offset (string)

Offset of the first object in this set (skipped items). This value must a multiple of maxnumberofitems.

Default value : 0

### Example

<https://api.politie.nl/v4/wijkagenten?language=nl&lat=53.1511173&lon=6.7566345999999984&radius=5.0&maxnumberofitems=10&offset=0>

### Responses

200: successful operation

Example Value

```

Model
{
  "iterator": {
    "last": true,
    "offset": 0
  },
  "wijkagenten": [

```

```

{
  "name": "string",
  "displayName": "string",
  "path": "string",
  "primaryNodeTypeName": "string",
  "leaf": true,
  "links": [
    {
      "rel": "string",
      "type": "string",
      "href": "string",
      "title": "string"
    }
  ],
  "canonicalHandleUuid": "string",
  "localizedName": "string",
  "uid": "string",
  "publicatieDatum": "string",
  "url": "string",
  "translations": [
    {
      "language": "string",
      "id": "string"
    }
  ],
  "naam": "string",
  "afbeelding": {
    "url": "string",
    "altText": "string"
  },
  "telefoon": "string",
  "twitter": {
    "accountNaam": "string",
    "list": "string",
    "title": "string"
  },
  "facebookUrl": "string",
  "werkgebied": "string",
  "extraInformatie": "string",
  "locaties": [
    {
      "latitude": 0,
      "longitude": 0
    }
  ],
  "werkgebiedPolygoon": "string",
  "instagramUrl": "string"
}
]
}

```

204: No results found

400: Invalid parameter

Example Value

Model

```
{
```

```

"code": 0,
"type": "string",
"message": "string",
"invalidFields": [
  "string"
]
}

```

## 6. **lv5/gezocht-zaak**

Search a single APB by UID.

### **Parameters**

uid (string)

Uid of document or page

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

Default value : nl

x-api-key (String)(header)

This service can only be used if you add a key value to your headers with label 'x-api-key'. Please contact us for a valid key.

### **Responses**

200: successful operation

Example Value

Model

```

[
  {}
]

```

204: No results found

400: Invalid parameter

Example Value

Model

```

{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}

```

403: Invalid API key

Example Value

Model

```

{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [

```

```
"string"
]
}
```

## 7. *lv5/vermist-zaak*

Search a single missing person by UID.

### **Parameters**

uid (string)  
Uid of document or page

language (string)  
Select objects in given (valid) language. Defaults to 'nl'.  
Default value : nl

x-api-key (String)(header)  
This service can only be used if you add a key value to your headers with label 'x-api-key'. Please contact us for a valid key.

### **Responses**

200: successful operation

Example Value

Model

```
[
  {}
]
```

204: No results found

400: Invalid parameter

Example Value

Model

```
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```

403: Invalid API key

Example Value

Model

```
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```

## 8. *lv5/gezocht*

Search all APB's. Results are sorted on descending date (newest first).

### **Parameters**

types (string)

Filter by types, a comma-separated list of types.

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

lat (number(\$double))

Latitude of the GPS coordinate used for search.

lon (number(\$double))

Longitude of the GPS coordinate used for search.

radius (number(\$double))

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

maxnumberofitems (integer(\$int32))

Maximum number of objects to return. Allowed values are 10 (default) and 25.

offset (integer(\$int32))

Offset of the first object in this set (skipped items). This value must a multiple of maxnumberofitems.

Default value : 0

x-api-key (String)(header)

This service can only be used if you add a key value to your headers with label 'x-api-key'. Please contact us for a valid key.

### **Responses**

200: successful operation

Example Value

Model

```
[
  {}
]
```

204: No results found

400: Invalid parameter

Example Value

Model

```
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```

403: Invalid API key

Example Value

Model

```
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```

## 9. *lv5/gezocht/eigenaar-gezocht*

Search APB's on stolen and recovered goods. Results are sorted on descending date (newest first).

### **Parameters**

types (string)

Filter by types, a comma-separated list of types.

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

lat (number(\$double))

Latitude of the GPS coordinate used for search.

lon (number(\$double))

Longitude of the GPS coordinate used for search.

radius (number(\$double))

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

maxnumberofitems (integer(\$int32))

Maximum number of objects to return. Allowed values are 10 (default) and 25.

offset (integer(\$int32))

Offset of the first object in this set (skipped items). This value must a multiple of maxnumberofitems.

Default value : 0

x-api-key (String)(header)

This service can only be used if you add a key value to your headers with label 'x-api-key'. Please contact us for a valid key.

### **Responses**

200: successful operation

Example Value

Model

```
[
  {}
]
```

204: No results found

400: Invalid parameter

Example Value

```
Model
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```

403: Invalid API key

```
Example Value
Model
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```

## 10. /v5/gezocht/opsporingsbericht

Search wanted persons. Results are sorted on descending date (newest first).

### **Parameters**

types (string)

Filter by types, a comma-separated list of types.

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

lat (number(\$double))

Latitude of the GPS coordinate used for search.

lon (number(\$double))

Longitude of the GPS coordinate used for search.

radius (number(\$double))

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

maxnumberofitems (integer(\$int32))

Maximum number of objects to return. Allowed values are 10 (default) and 25.

offset (integer(\$int32))

Offset of the first object in this set (skipped items). This value must a multiple of maxnumberofitems.

Default value : 0

x-api-key (String)(header)

This service can only be used if you add a key value to your headers with label 'x-api-key'. Please contact us for a valid key.

### **Responses**

200: successful operation

Example Value

Model

```
[
  {}
]
```

204: No results found

400: Invalid parameter

Example Value

Model

```
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```

403: Invalid API key

Example Value

Model

```
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```

## 11. **/v5/gezocht/nationale-opsporingslijst**

Search fugitive APB's. Results are sorted on descending date (newest first).

### **Parameters**

types (string)

Filter by types, a comma-separated list of types.

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

lat (number(\$double))

Latitude of the GPS coordinate used for search.

lon (number(\$double))

Longitude of the GPS coordinate used for search.

radius (number(\$double))

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

maxnumberofitems (integer(\$int32))

Maximum number of objects to return. Allowed values are 10 (default) and 25.

offset (integer(\$int32))

Offset of the first object in this set (skipped items). This value must be a multiple of maxnumberofitems.

Default value : 0

x-api-key (String)(header)

This service can only be used if you add a key value to your headers with label 'x-api-key'. Please contact us for a valid key.

## **Responses**

200: successful operation

Example Value

Model

```
[
  {}
]
```

204: No results found

400: Invalid parameter

Example Value

Model

```
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```

403: Invalid API key

Example Value

Model

```
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```

## **12. /v5/gezocht/getuigenoproep**

Search calls for witnesses. Results are sorted on descending date (newest first).

## **Parameters**

types (string)

Filter by types, a comma-separated list of types.

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

lat (number(\$double))

Latitude of the GPS coordinate used for search.

lon (number(\$double))

Longitude of the GPS coordinate used for search.

radius (number(\$double))

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

maxnumberofitems (integer(\$int32))

Maximum number of objects to return. Allowed values are 10 (default) and 25.

offset (integer(\$int32))

Offset of the first object in this set (skipped items). This value must a multiple of maxnumberofitems.

Default value : 0

x-api-key (String)(header)

This service can only be used if you add a key value to your headers with label 'x-api-key'. Please contact us for a valid key.

## **Responses**

200: successful operation

Example Value

Model

```
[
  {}
]
```

204: No results found

400: Invalid parameter

Example Value

Model

```
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```

403: Invalid API key

Example Value

Model

```
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
```

```

    "string"
  ]
}

```

### 13. *lv5/vermist*

Search all missing persons. Results are sorted on descending date (newest first).

#### **Parameters**

types (string)

Filter by types, a comma-separated list of types.

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

lat (number(\$double))

Latitude of the GPS coordinate used for search.

lon (number(\$double))

Longitude of the GPS coordinate used for search.

radius (number(\$double))

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

maxnumberofitems (integer(\$int32))

Maximum number of objects to return. Allowed values are 10 (default) and 25.

offset (integer(\$int32))

Offset of the first object in this set (skipped items). This value must a multiple of maxnumberofitems.

Default value : 0

x-api-key (String)(header)

This service can only be used if you add a key value to your headers with label 'x-api-key'. Please contact us for a valid key.

#### **Responses**

200: successful operation

Example Value

Model

```

[
  {}
]

```

204: No results found

400: Invalid parameter

Example Value

Model

```

{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [

```

```
"string"
]
}
```

403: Invalid API key

Example Value

Model

```
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```

#### 14. *lv5/vermist/ongeachteerde-personen*

Search unidentified persons. Results are sorted on descending date (newest first).

##### **Parameters**

types (string)

Filter by types, a comma-separated list of types.

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

lat (number(\$double))

Latitude of the GPS coordinate used for search.

lon (number(\$double))

Longitude of the GPS coordinate used for search.

radius (number(\$double))

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

maxnumberofitems (integer(\$int32))

Maximum number of objects to return. Allowed values are 10 (default) and 25.

offset (integer(\$int32))

Offset of the first object in this set (skipped items). This value must be a multiple of maxnumberofitems.

Default value : 0

x-api-key (String)(header)

This service can only be used if you add a key value to your headers with label 'x-api-key'. Please contact us for a valid key.

##### **Responses**

200: successful operation

Example Value

Model

```
[
  {}
]
```

]

204: No results found

400: Invalid parameter

Example Value

Model

```
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```

403: Invalid API key

Example Value

Model

```
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```

## 15. *lv5/urgentpolitiebericht*

Shows all urgent APBs when issued, for broadcast e.g. on TV.

### **Parameters**

x-api-key (String)(header)

This service can only be used if you add a key value to your headers with label 'x-api-key'. Please contact us for a valid key.

### **Responses**

200: successful operation

Example Value

Model

```
[
  {}
]
```

204: No results found

400: Invalid parameter

Example Value

Model

```
{
  "code": 0,
```

```
"type": "string",
"message": "string",
"invalidFields": [
  "string"
]
}
```

403: Invalid API key

Example Value

Model

```
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```

```
+++++
OUD
+++++
```

## 16. /v4/gezocht

Search a single APB by UID.

### Parameters

uid (string)

Uid of document or page

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

Default value : nl

query (string)

Terms to query for. Length of the query is limited to 100 characters.

lat (string)

Latitude of the GPS coordinate used for search.

lon (string)

Longitude of the GPS coordinate used for search.

radius (string)

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

Default value : 5.0

maxnumberofitems (string)

Maximum number of objects to return. Allowed values are 10 (default) and 25.

Default value : 10

offset (string)

Offset of the first object in this set (skipped items). This value must a multiple of maxnumberofitems.

Default value : 0

### 17. /v4/gezocht/gezochtepersonen

Search all APB's on persons. Results can be fugitives and wanted persons. Most wanted persons are not included in this list and can be retrieved using the method 'gezocht/nationaleopsporingslijst'. Results are sorted on descending date (newest first).

#### Parameters

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

Default value : nl

query (string)

Terms to query for. Length of the query is limited to 100 characters.

lat (string)

Latitude of the GPS coordinate used for search.

lon (string)

Longitude of the GPS coordinate used for search.

radius (string)

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

Default value : 5.0

maxnumberofitems (string)

Maximum number of objects to return. Allowed values are 10 (default) and 25.

Default value : 10

offset (string)

Offset of the first object in this set (skipped items). This value must a multiple of maxnumberofitems.

Default value : 0

#### Example

<https://api.politie.nl/v4/gezocht/gezochtepersonen?language=nl&radius=5.0&maxnumberofitems=10&offset=0>

#### Responses

200: successful operation

Example Value

Model

```
{
  "iterator": {
    "last": true,
    "offset": 0
  },
  "opsporingsberichten": [
    {
      "name": "string",
      "displayName": "string",
      "path": "string",
      "primaryNodeType": "string",
      "leaf": true,
      "links": [
        {
```

```
    "rel": "string",
    "type": "string",
    "href": "string",
    "title": "string"
  }
],
"canonicalHandleUuid": "string",
"localizedName": "string",
"uid": "string",
"publicatieDatum": "string",
"url": "string",
"translations": [
  {
    "language": "string",
    "id": "string"
  }
],
"titel": "string",
"zaaknummer": "string",
"afbeeldingen": [
  {
    "url": "string",
    "altText": "string"
  }
],
"introductie": "string",
"documentType": "string",
"omschrijving": "string",
"meerAfbeeldingen": [
  {
    "url": "string",
    "altText": "string"
  }
],
"urlTipformulier": "string",
"locaties": [
  {
    "latitude": 0,
    "longitude": 0
  }
],
"verdachteRepresentation": {
  "opgelost": true,
  "update": "string",
  "vraag": "string",
  "videos": [
    {
      "alineaType": "string",
      "url": "string",
      "captionTitle": "string",
      "captionSubTitle": "string"
    }
  ]
},
"datumDelict": "string",
"plaatsDelict": "string",
"signalementen": [
  {
    "titel": "string",
```

```
    "afbeelding": {
      "url": "string",
      "altText": "string"
    },
    "persoonskenmerken": [
      {
        "label": "string",
        "waarde": "string"
      }
    ]
  },
  ],
  "slachtoffer": true
},
"voortvluchtigeRepresentation": {
  "opgelost": true,
  "update": "string",
  "vraag": "string",
  "videos": [
    {
      "alineaType": "string",
      "url": "string",
      "captionTitle": "string",
      "captionSubTitle": "string"
    }
  ],
  "laatsteVerblijfplaats": "string",
  "persoonskenmerken": [
    {
      "label": "string",
      "waarde": "string"
    }
  ]
},
"gestolenGevondenRepresentation": {
  "opgelost": true,
  "update": "string",
  "vraag": "string",
  "videos": [
    {
      "alineaType": "string",
      "url": "string",
      "captionTitle": "string",
      "captionSubTitle": "string"
    }
  ],
  "datumDelict": "string",
  "plaatsDelict": "string"
},
"dossierRepresentation": {
  "datumDelict": "string",
  "plaatsDelict": "string",
  "zaakContent": [
    {
      "alineaType": "string"
    }
  ],
  "slachtoffer": true
}
```

```
    }  
  }  
]  
}  
204: No results found
```

400: Invalid parameter

Example Value

Model

```
{  
  "code": 0,  
  "type": "string",  
  "message": "string",  
  "invalidFields": [  
    "string"  
  ]  
}
```

### 18. /v4/gezocht/nationaleopsporingslijst

Search most wanted fugitives APB's. Results are sorted on descending date (newest first).

#### **Parameters**

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

Default value : nl

query (string)

Terms to query for. Length of the query is limited to 100 characters.

lat (string)

Latitude of the GPS coordinate used for search.

lon (string)

Longitude of the GPS coordinate used for search.

radius (string)

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

Default value : 5.0

maxnumberofitems (string)

Maximum number of objects to return. Allowed values are 10 (default) and 25.

Default value : 10

offset (string)

Offset of the first object in this set (skipped items). This value must a multiple of maxnumberofitems.

Default value : 0

#### **Example**

<https://api.politie.nl/v4/gezocht/nationaleopsporingslijst?language=nl&radius=5.0&maxnumberofitems=10&offset=10>

#### **Responses**

200: successful operation

Example Value

Model

```
{
  "iterator": {
    "last": true,
    "offset": 0
  },
  "opsporingsberichten": [
    {
      "name": "string",
      "displayName": "string",
      "path": "string",
      "primaryNodeTypeName": "string",
      "leaf": true,
      "links": [
        {
          "rel": "string",
          "type": "string",
          "href": "string",
          "title": "string"
        }
      ],
      "canonicalHandleUuid": "string",
      "localizedName": "string",
      "uid": "string",
      "publicatieDatum": "string",
      "url": "string",
      "translations": [
        {
          "language": "string",
          "id": "string"
        }
      ],
      "titel": "string",
      "zaaknummer": "string",
      "afbeeldingen": [
        {
          "url": "string",
          "altText": "string"
        }
      ],
      "introducectie": "string",
      "documentType": "string",
      "omschrijving": "string",
      "meerAfbeeldingen": [
        {
          "url": "string",
          "altText": "string"
        }
      ],
      "urlTipformulier": "string",
      "locaties": [
        {
          "latitude": 0,
          "longitude": 0
        }
      ],
      "verdachteRepresentation": {
        "opgelost": true,
        "update": "string",

```

```
"vraag": "string",
"videos": [
  {
    "alineatype": "string",
    "url": "string",
    "captionTitle": "string",
    "captionSubTitle": "string"
  }
],
"datumDelict": "string",
"plaatsDelict": "string",
"signalementen": [
  {
    "titel": "string",
    "afbeelding": {
      "url": "string",
      "altText": "string"
    },
    "persoonskenmerken": [
      {
        "label": "string",
        "waarde": "string"
      }
    ]
  }
],
"slachtoffer": true
},
"voortvluchtigeRepresentation": {
  "opgelost": true,
  "update": "string",
  "vraag": "string",
  "videos": [
    {
      "alineatype": "string",
      "url": "string",
      "captionTitle": "string",
      "captionSubTitle": "string"
    }
  ],
  "laatsteVerblijfplaats": "string",
  "persoonskenmerken": [
    {
      "label": "string",
      "waarde": "string"
    }
  ]
},
"gestolenGevondenRepresentation": {
  "opgelost": true,
  "update": "string",
  "vraag": "string",
  "videos": [
    {
      "alineatype": "string",
      "url": "string",
      "captionTitle": "string",
      "captionSubTitle": "string"
    }
  ]
}
```

```

    }
  ],
  "datumDelict": "string",
  "plaatsDelict": "string"
},
"dossierRepresentation": {
  "datumDelict": "string",
  "plaatsDelict": "string",
  "zaakContent": [
    {
      "alineatype": "string"
    }
  ],
  "slachtoffer": true
}
}
]
}

```

204: No results found

400: Invalid parameter

Example Value

Model

```

{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}

```

## 19. /v4/gezocht/eigenaargezocht

Search APB's on stolen and recovered goods. Results are sorted on descending date (newest first).

### Parameters

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

Default value : nl

query (string)

Terms to query for. Length of the query is limited to 100 characters.

lat (string)

Latitude of the GPS coordinate used for search.

lon (string)

Longitude of the GPS coordinate used for search.

radius (string)

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

Default value : 5.0

maxnumberofitems (string)

Maximum number of objects to return. Allowed values are 10 (default) and 25.

Default value : 10

offset (string)

Offset of the first object in this set (skipped items). This value must a multiple of maxnumberofitems.

Default value : 0

### Example

<https://api.politie.nl/v4/gezocht/eigenaargezocht?language=nl&radius=5.0&maxnumberofitems=10&offset=0>

### Responses

200: successful operation

Example Value

Model

```
{
  "iterator": {
    "last": true,
    "offset": 0
  },
  "opsporingsberichten": [
    {
      "name": "string",
      "displayName": "string",
      "path": "string",
      "primaryNodeTypeName": "string",
      "leaf": true,
      "links": [
        {
          "rel": "string",
          "type": "string",
          "href": "string",
          "title": "string"
        }
      ],
      "canonicalHandleUuid": "string",
      "localizedName": "string",
      "uid": "string",
      "publicatieDatum": "string",
      "url": "string",
      "translations": [
        {
          "language": "string",
          "id": "string"
        }
      ],
      "titel": "string",
      "zaaknummer": "string",
      "afbeeldingen": [
        {
          "url": "string",
          "altText": "string"
        }
      ],
      "introducectie": "string",
      "documentType": "string",
      "omschrijving": "string",
      "meerAfbeeldingen": [
        {
          "url": "string",
```

```
    "altText": "string"
  }
],
"urlTipformulier": "string",
"locaties": [
  {
    "latitude": 0,
    "longitude": 0
  }
],
"verdachteRepresentation": {
  "opgelost": true,
  "update": "string",
  "vraag": "string",
  "videos": [
    {
      "alineatype": "string",
      "url": "string",
      "captionTitle": "string",
      "captionSubTitle": "string"
    }
  ],
  "datumDelict": "string",
  "plaatsDelict": "string",
  "signalementen": [
    {
      "titel": "string",
      "afbeelding": {
        "url": "string",
        "altText": "string"
      },
      "persoonskenmerken": [
        {
          "label": "string",
          "waarde": "string"
        }
      ]
    }
  ]
},
"slachtoffer": true
},
"voortvluchtigeRepresentation": {
  "opgelost": true,
  "update": "string",
  "vraag": "string",
  "videos": [
    {
      "alineatype": "string",
      "url": "string",
      "captionTitle": "string",
      "captionSubTitle": "string"
    }
  ],
  "laatsteVerblijfplaats": "string",
  "persoonskenmerken": [
    {
      "label": "string",
      "waarde": "string"
    }
  ]
}
```

```

    }
  ]
},
"gestolenGevondenRepresentation": {
  "opgelost": true,
  "update": "string",
  "vraag": "string",
  "videos": [
    {
      "alineatype": "string",
      "url": "string",
      "captionTitle": "string",
      "captionSubTitle": "string"
    }
  ],
  "datumDelict": "string",
  "plaatsDelict": "string"
},
"dossierRepresentation": {
  "datumDelict": "string",
  "plaatsDelict": "string",
  "zaakContent": [
    {
      "alineatype": "string"
    }
  ],
  "slachtoffer": true
}
}
]
}
204: No results found

```

400: Invalid parameter

Example Value

Model

```

{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}

```

## 20. /v4/gezocht/dossiers

Search case files. Results are sorted on descending date (newest first).

### Parameters

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

Default value : nl

query (string)

Terms to query for. Length of the query is limited to 100 characters.

lat (string)

Latitude of the GPS coordinate used for search.

lon (string)

Longitude of the GPS coordinate used for search.

radius (string)

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

Default value : 5.0

maxnumberofitems (string)

Maximum number of objects to return. Allowed values are 10 (default) and 25.

Default value : 10

offset (string)

Offset of the first object in this set (skipped items). This value must a multiple of maxnumberofitems.

Default value : 0

### **Example**

<https://api.politie.nl/v4/gezocht/dossiers?language=nl&radius=5.0&maxnumberofitems=10&offset=0>

### **Responses**

200: successful operation

Example Value

Model

```
{
  "iterator": {
    "last": true,
    "offset": 0
  },
  "opsporingsberichten": [
    {
      "name": "string",
      "displayName": "string",
      "path": "string",
      "primaryNodeTypeName": "string",
      "leaf": true,
      "links": [
        {
          "rel": "string",
          "type": "string",
          "href": "string",
          "title": "string"
        }
      ],
      "canonicalHandleUuid": "string",
      "localizedName": "string",
      "uid": "string",
      "publicatieDatum": "string",
      "url": "string",
      "translations": [
        {
          "language": "string",
          "id": "string"
        }
      ],
      "titel": "string",
```

```
"zaaknummer": "string",
"afbeeldingen": [
  {
    "url": "string",
    "altText": "string"
  }
],
"introductie": "string",
"documentType": "string",
"omschrijving": "string",
"meerAfbeeldingen": [
  {
    "url": "string",
    "altText": "string"
  }
],
"urlTipformulier": "string",
"locaties": [
  {
    "latitude": 0,
    "longitude": 0
  }
],
"verdachteRepresentation": {
  "opgelost": true,
  "update": "string",
  "vraag": "string",
  "videos": [
    {
      "alineaType": "string",
      "url": "string",
      "captionTitle": "string",
      "captionSubTitle": "string"
    }
  ],
  "datumDelict": "string",
  "plaatsDelict": "string",
  "signalementen": [
    {
      "titel": "string",
      "afbeelding": {
        "url": "string",
        "altText": "string"
      },
      "persoonskenmerken": [
        {
          "label": "string",
          "waarde": "string"
        }
      ]
    }
  ]
},
"slachtoffer": true
},
"voortvluchtigeRepresentation": {
  "opgelost": true,
  "update": "string",
  "vraag": "string",
```

```

    "videos": [
      {
        "alineatype": "string",
        "url": "string",
        "captionTitle": "string",
        "captionSubTitle": "string"
      }
    ],
    "laatsteVerblijfplaats": "string",
    "persoonskenmerken": [
      {
        "label": "string",
        "waarde": "string"
      }
    ]
  },
  "gestolenGevondenRepresentation": {
    "opgelost": true,
    "update": "string",
    "vraag": "string",
    "videos": [
      {
        "alineatype": "string",
        "url": "string",
        "captionTitle": "string",
        "captionSubTitle": "string"
      }
    ],
    "datumDelict": "string",
    "plaatsDelict": "string"
  },
  "dossierRepresentation": {
    "datumDelict": "string",
    "plaatsDelict": "string",
    "zaakContent": [
      {
        "alineatype": "string"
      }
    ],
    "slachtoffer": true
  }
}

```

204: No results found

400: Invalid parameter

Example Value

Model

```

{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}

```

## 21. /v4/vermist

Search missing persons (without unidentified persons). Use consecutive methods to retrieve missing children, adults or unidentified persons. Results are sorted on descending date (newest first).

### Parameters

uid (string)

Uid of document or page

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

Default value : nl

query (string)

Terms to query for. Length of the query is limited to 100 characters.

lat (string)

Latitude of the GPS coordinate used for search.

lon (string)

Longitude of the GPS coordinate used for search.

radius (string)

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

Default value : 5.0

maxnumberofitems (string)

Maximum number of objects to return. Allowed values are 10 (default) and 25.

Default value : 10

offset (string)

Offset of the first object in this set (skipped items). This value must a multiple of maxnumberofitems.

Default value : 0

### Example

<https://api.politie.nl/v4/vermist?language=nl&radius=5.0&maxnumberofitems=10&offset=0>

### Responses

200: successful operation

Example Value

Model

```
{
  "iterator": {
    "last": true,
    "offset": 0
  },
  "vermisten": [
    {
      "name": "string",
      "displayName": "string",
      "path": "string",
      "primaryNodeType": "string",
      "leaf": true,
      "links": [
        {
```

```
    "rel": "string",
    "type": "string",
    "href": "string",
    "title": "string"
  }
],
"canonicalHandleUuid": "string",
"localizedName": "string",
"uid": "string",
"publicatieDatum": "string",
"url": "string",
"translations": [
  {
    "language": "string",
    "id": "string"
  }
],
"documentType": "string",
"titel": "string",
"zaaknummer": "string",
"vermistSinds": "string",
"laatstGezienIn": "string",
"afbeeldingen": [
  {
    "url": "string",
    "altText": "string"
  }
],
"signalementen": [
  {
    "titel": "string",
    "afbeelding": {
      "url": "string",
      "altText": "string"
    },
    "persoonskenmerken": [
      {
        "label": "string",
        "waarde": "string"
      }
    ]
  }
],
"introducectie": "string",
"omschrijving": "string",
"vragen": "string",
"meerAfbeeldingen": [
  {
    "url": "string",
    "altText": "string"
  }
],
"locaties": [
  {
    "latitude": 0,
    "longitude": 0
  }
],
```

```

    "videos": [
      {
        "alineatype": "string",
        "url": "string",
        "captionTitle": "string",
        "captionSubTitle": "string"
      }
    ],
    "uwTip": "string",
    "urlTipformulier": "string"
  }
]
}

```

204: No results found

400: Invalid parameter

Example Value

Model

```

{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}

```

## 22. /v4/vermist/vermistekinderen

Search missing children. Results are sorted on descending date (newest first).

### Parameters

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

Default value : nl

query (string)

Terms to query for. Length of the query is limited to 100 characters.

lat (string)

Latitude of the GPS coordinate used for search.

lon (string)

Longitude of the GPS coordinate used for search.

radius (string)

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

Default value : 5.0

maxnumberofitems (string)

Maximum number of objects to return. Allowed values are 10 (default) and 25.

Default value : 10

offset (string)

Offset of the first object in this set (skipped items). This value must a multiple of maxnumberofitems.

Default value : 0

### Example

<https://api.politie.nl/v4/vermist/vermistekinderen?language=nl&radius=5.0&maxnumberofitems=10&offset=0>

### Responses

200: successful operation

Example Value

Model

```
{
  "iterator": {
    "last": true,
    "offset": 0
  },
  "vermisten": [
    {
      "name": "string",
      "displayName": "string",
      "path": "string",
      "primaryNodeTypeName": "string",
      "leaf": true,
      "links": [
        {
          "rel": "string",
          "type": "string",
          "href": "string",
          "title": "string"
        }
      ],
      "canonicalHandleUuid": "string",
      "localizedName": "string",
      "uid": "string",
      "publicatieDatum": "string",
      "url": "string",
      "translations": [
        {
          "language": "string",
          "id": "string"
        }
      ],
      "documentType": "string",
      "titel": "string",
      "zaaknummer": "string",
      "vermistSinds": "string",
      "laatstGezienIn": "string",
      "afbeeldingen": [
        {
          "url": "string",
          "altText": "string"
        }
      ],
      "signalementen": [
        {
          "titel": "string",
          "afbeelding": {
            "url": "string",
            "altText": "string"
          }
        }
      ]
    }
  ]
}
```

```

        "persoonskenmerken": [
            {
                "label": "string",
                "waarde": "string"
            }
        ]
    },
    "introductie": "string",
    "omschrijving": "string",
    "vragen": "string",
    "meerAfbeeldingen": [
        {
            "url": "string",
            "altText": "string"
        }
    ],
    "locaties": [
        {
            "latitude": 0,
            "longitude": 0
        }
    ],
    "videos": [
        {
            "alineaType": "string",
            "url": "string",
            "captionTitle": "string",
            "captionSubTitle": "string"
        }
    ],
    "uwTip": "string",
    "urlTipformulier": "string"
}
]
}

```

204: No results found

400: Invalid parameter

Example Value

Model

```

{
    "code": 0,
    "type": "string",
    "message": "string",
    "invalidFields": [
        "string"
    ]
}

```

### 23. *lv4/vermist/vermistevolwassenen*

Search missing adults. Results are sorted on descending date (newest first).

#### **Parameters**

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

Default value : nl

query (string)

Terms to query for. Length of the query is limited to 100 characters.

lat (string)

Latitude of the GPS coordinate used for search.

lon (string)

Longitude of the GPS coordinate used for search.

radius (string)

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

Default value : 5.0

maxnumberofitems (string)

Maximum number of objects to return. Allowed values are 10 (default) and 25.

Default value : 10

offset (string)

Offset of the first object in this set (skipped items). This value must a multiple of maxnumberofitems.

Default value : 0

### **Example**

<https://api.politie.nl/v4/vermist/vermistevolwassenen?language=nl&radius=5.0&maxnumberofitems=10&offset=0>

### **Responses**

200: successful operation

Example Value

Model

```
{
  "iterator": {
    "last": true,
    "offset": 0
  },
  "vermisten": [
    {
      "name": "string",
      "displayName": "string",
      "path": "string",
      "primaryNodeTypeName": "string",
      "leaf": true,
      "links": [
        {
          "rel": "string",
          "type": "string",
          "href": "string",
          "title": "string"
        }
      ],
      "canonicalHandleUuid": "string",
      "localizedName": "string",
      "uid": "string",
      "publicatieDatum": "string",
      "url": "string",
      "translations": [
        {
          "language": "string",
```

```
    "id": "string"
  },
],
"documentType": "string",
"titel": "string",
"zaaknummer": "string",
"vermistSinds": "string",
"laatstGezienIn": "string",
"afbeeldingen": [
  {
    "url": "string",
    "altText": "string"
  }
],
"signalelementen": [
  {
    "titel": "string",
    "afbeelding": {
      "url": "string",
      "altText": "string"
    },
    "persoonskenmerken": [
      {
        "label": "string",
        "waarde": "string"
      }
    ]
  }
],
"introdunctie": "string",
"omschrijving": "string",
"vragen": "string",
"meerAfbeeldingen": [
  {
    "url": "string",
    "altText": "string"
  }
],
"locaties": [
  {
    "latitude": 0,
    "longitude": 0
  }
],
"videos": [
  {
    "alineatype": "string",
    "url": "string",
    "captionTitle": "string",
    "captionSubTitle": "string"
  }
],
"uwTip": "string",
"urlTipformulier": "string"
}
]
```

204: No results found

400: Invalid parameter

Example Value

Model

```
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```

#### **24. /v4/vermist/ongeidificeerd**

Search unidentified persons. Results are sorted on descending date (newest first).

##### **Parameters**

uid (string)

Uid of document or page

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

Default value : nl

query (string)

Terms to query for. Length of the query is limited to 100 characters.

lat (string)

Latitude of the GPS coordinate used for search.

lon (string)

Longitude of the GPS coordinate used for search.

radius (string)

Radius in kilometer around the given GPS coordinate to search for objects. Allowed values are: 0.5, 2.0, 5.0 (default), 10.0 and 25.0.

Default value : 5.0

maxnumberofitems (string)

Maximum number of objects to return. Allowed values are 10 (default) and 25.

Default value : 10

offset (string)

Offset of the first object in this set (skipped items). This value must a multiple of maxnumberofitems.

Default value : 0

##### **Example**

<https://api.politie.nl/v4/vermist/ongeidificeerd?language=nl&radius=5.0&maxnumberofitems=10&offset=0>

##### **Responses**

200: successful operation

Example Value

Model

```
{
  "iterator": {
```

```
"last": true,
"offset": 0
},
"ongeidentificeerden": [
{
  "name": "string",
  "displayName": "string",
  "path": "string",
  "primaryNodeTypeName": "string",
  "leaf": true,
  "links": [
    {
      "rel": "string",
      "type": "string",
      "href": "string",
      "title": "string"
    }
  ],
  "canonicalHandleUuid": "string",
  "localizedName": "string",
  "uid": "string",
  "publicatieDatum": "string",
  "url": "string",
  "translations": [
    {
      "language": "string",
      "id": "string"
    }
  ],
  "titel": "string",
  "zaaknummer": "string",
  "gevondenOpDatum": "string",
  "vindplaats": "string",
  "afbeeldingen": [
    {
      "url": "string",
      "altText": "string"
    }
  ],
  "signalementen": [
    {
      "titel": "string",
      "afbeelding": {
        "url": "string",
        "altText": "string"
      },
      "persoonskenmerken": [
        {
          "label": "string",
          "waarde": "string"
        }
      ]
    }
  ],
  "introdactie": "string",
  "omschrijving": "string",
  "vragen": "string",
  "meerAfbeeldingen": [
```

```

    {
      "url": "string",
      "altText": "string"
    }
  ],
  "locaties": [
    {
      "latitude": 0,
      "longitude": 0
    }
  ],
  "videos": [
    {
      "alineatype": "string",
      "url": "string",
      "captionTitle": "string",
      "captionSubTitle": "string"
    }
  ],
  "uwTip": "string",
  "urlTipformulier": "string",
  "blurlImage": true
}
]
}

```

204: No results found

400: Invalid parameter

Example Value

Model

```

{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}

```

## 25. /v4/urgentpolitiebericht

Shows max. one urgent APB when issued, for broadcast e.g. on TV.

### Parameters

language (string)

Select objects in given (valid) language. Defaults to 'nl'.

Default value : nl

### Example

<https://api.politie.nl/v4/urgentpolitiebericht?language=nl>

### Responses

200: successful operation

Example Value

Model

```

{

```

```
"iterator": {
  "last": true,
  "offset": 0
},
"opsporingsberichten": [
  {
    "name": "string",
    "displayName": "string",
    "path": "string",
    "primaryNodeTypeName": "string",
    "leaf": true,
    "links": [
      {
        "rel": "string",
        "type": "string",
        "href": "string",
        "title": "string"
      }
    ],
    "canonicalHandleUuid": "string",
    "localizedName": "string",
    "uid": "string",
    "publicatieDatum": "string",
    "url": "string",
    "translations": [
      {
        "language": "string",
        "id": "string"
      }
    ],
    "titel": "string",
    "zaaknummer": "string",
    "afbeeldingen": [
      {
        "url": "string",
        "altText": "string"
      }
    ],
    "introducectie": "string",
    "documentType": "string",
    "omschrijving": "string",
    "meerAfbeeldingen": [
      {
        "url": "string",
        "altText": "string"
      }
    ],
    "urlTipformulier": "string",
    "locaties": [
      {
        "latitude": 0,
        "longitude": 0
      }
    ],
    "verdachteRepresentation": {
      "opgelost": true,
      "update": "string",
      "vraag": "string",
```

```
"videos": [
  {
    "alineaType": "string",
    "url": "string",
    "captionTitle": "string",
    "captionSubTitle": "string"
  }
],
"datumDelict": "string",
"plaatsDelict": "string",
"signalementen": [
  {
    "titel": "string",
    "afbeelding": {
      "url": "string",
      "altText": "string"
    },
    "persoonskenmerken": [
      {
        "label": "string",
        "waarde": "string"
      }
    ]
  }
],
"slachtoffer": true
},
"voortvluchtigeRepresentation": {
  "opgelost": true,
  "update": "string",
  "vraag": "string",
  "videos": [
    {
      "alineaType": "string",
      "url": "string",
      "captionTitle": "string",
      "captionSubTitle": "string"
    }
  ],
  "laatsteVerblijfplaats": "string",
  "persoonskenmerken": [
    {
      "label": "string",
      "waarde": "string"
    }
  ]
},
"gestolenGevondenRepresentation": {
  "opgelost": true,
  "update": "string",
  "vraag": "string",
  "videos": [
    {
      "alineaType": "string",
      "url": "string",
      "captionTitle": "string",
      "captionSubTitle": "string"
    }
  ]
}
```

```
    ],
    "datumDelict": "string",
    "plaatsDelict": "string"
  },
  "dossierRepresentation": {
    "datumDelict": "string",
    "plaatsDelict": "string",
    "zaakContent": [
      {
        "alineatype": "string"
      }
    ],
    "slachtoffer": true
  }
}
]
```

204: No results found

400: Invalid parameter

Example Value

Model

```
{
  "code": 0,
  "type": "string",
  "message": "string",
  "invalidFields": [
    "string"
  ]
}
```